

NEW!
WATERPROOF

LaMotte

DC1500 Chlorine Colorimeter

Available in Tablet or Liquid Versions

 Waterproof  USB Capable  Rechargeable



DC1500 Chlorine Colorimeter Kit

Order Code 3240 (tablet) or Order Code 3240-LI (liquid) |
Kit Refills: Order Code R-3240 (tablet) | or Order Code R-3240-LI (liquid) |

- **Field & Lab Use:** USB cable and wall adapter included; car charger optional
- **Rechargeable battery:** No need to buy batteries again
- **EPA Compliant:** Uses proper wavelength and DPD test method to meet EPA design specifications for NPDWR and NPDES chlorine monitoring programs (EPA 330.5 and Standard Method 4500)
- **0-4 ppm Chlorine:** No need to select a low or high range. The DC1500 covers the entire critical chlorine range of 0-4 ppm with an MDL of 0.03 ppm.
- **A Great Value:** Complete, economical package! The DC1500 Chlorine Colorimeter Kit includes tablets for 100 tests or liquid reagents for 140 tests, six sample vials, and a sturdy carrying case.
- **IP67 Waterproof Design:** Designed with excessive exposure to moisture in mind, the DC1500 colorimeter delivers trouble-free performance
- Bold, backlit display
- European CE Mark
- USB port

STANDARD
METHODS
4500

IP67
WATERPROOF

EPA
330.5

2 YEAR
WARRANTY

CE

durable
CASE

Industry-Leading Precision, Sensitivity, & Dependability!

Features include:

- Large graphical liquid crystal display
- Simple, menu-driven operation
- Lithium ion rechargeable battery and computer/wall adapter
- IP67 Waterproof
- Backlit display
- Auto-off
- USB port
- European CE mark



Additional advancements include:

- Superior narrow band-width interference filters
- Optional software for data storage and manipulation

DC1500 Chlorine Colorimeter Kit

Order Code 3240 [tablet] or Order Code 3240-LI [liquid]

Kit Refills

Order Code R-3240 [tablet]

Order Code R-3240-LI [liquid]

Readout:	160 x 100 backlit LCD, 20 x 6 line graphical display
Wavelength Accuracy:	±2% FS
Wavelength Bandwidth:	10 nm typical
Light Source:	LED
Detector:	Silicon photodiode with integrated interference filter
Modes:	Pre-programmed test, absorbance, %T
Languages:	English, Spanish, French, Portuguese, Italian, Chinese, Japanese
Sample Chamber:	25 mm diameter flat bottom test tubes
USB Port:	Mini USB
Power:	Lithium ion rechargeable battery, 3.7v, 2.5 x .75 inches, 1.7 oz. or USB computer cable or wall adapter
Battery:	Charge Life: Approx. 380 tests with backlight on to 1000 tests with backlight off.
Battery Life:	Approx. 500 charges
Auto Shut-off:	Disabled, 5, 10, 50 minutes
CE Mark:	Yes
Shipping Weight	8 lbs
Shipping Size [LxWxH]	17 x 16 x 9



LaMotte Company · PO Box 329 · Chestertown · Maryland · 21620 · USA
t: 800-344-3100 · 410-778-3100 · f: 410-778-6394 · www.lamotte.com