



# **SOIL TESTING PRODUCTS**



# METERS & ACCESSORIES

## pН

Soil pH is a measure of the relative acidity or basicity of a given soil. The pH scale (0-14) is a logarithmic expression of hydrogen ion activity. A pH of 7.0 is neutral, and soils above or below this value are either alkaline or acidic, respectively. A soil with a pH of 6.0 is ten times more acidic than a soil of pH 7.0. Changes in soil pH dramatically affect the availability of nutrients to growing crops. The pH meter is the preferred method for determination of soil pH and the only one adaptable to the buffer methods for determining the lime requirement of a soil. pH is measured by mixing a 1:1 ratio of soil and distilled water. Distilled water not included with meters.

**€**LaMotte

рН 5

HOLD

Code 5-0035-01

OFF

CAL

MODE

# LaMotte pH 5 Series Meter

pH 5 (without case) · Code 5-0034-01 · NH (3)

#### pH 5 (with case) · Code 5-0035-01 · NH (5)

Meter includes electrode and temperature probe, pH 4, 7 and 10 buffer tablets, and is available with or without a carrying case.

#### Features:

- Range: 0.00-14.00 pH/0.01 pH
- Three point calibration
- Automatic Temperature Compensation
- Temperature readout 0-100°C/0.1°C
- Power: Four AAA batteries included
- Auto-off after 17 minutes
- Hold function
- Instructions included for measuring pH in soil

See back page for Shipping Codes & Weights chart.

Code 5-0034-02



# pH Buffer Solutions

These Standardized pH Buffer Solutions are for use in calibration of pH meters. Available in 120 mL and 500 mL sizes.

pH Value*	Code
4.01	2866
7.00	2881
10.00	2896

Other pH values available.



# **Buffer Tablets**

Add one tablet to 20 mL of Deionized Water to produce buffers. Available in 50 and 100 tablet packs. In foil strips of 10 tablets each.

Code
3983A
3984A
3985A

2

# pH Tracer

#### Code 1741 · NH (1)

Tracer provided with 4, 7 and 10 pH buffer tablets.

#### Features:

TRACER

8

15.3

PockeTester

MODE

CAL

....

ᅇᆎ

€LaMotte

Code 1741

TRACER

1 5 PockeTester MODE

> CAL ᅇᆎ

€LaMotte

- Range: 0.00 to 14.00 pH/0.01 pH
- Temp: 23° to 194°F (-5° to 90° C)
- Resolution: 0.01 pH
- Rugged flat surface electrode will alert user when it's time to "RENEW"
- A "CAL" indicator shows when to recalibrate and user can select a 1, 2, or 3 point calibration
- Includes Automatic Temperature Compensation and displays temperature while showing pH result
- Optional interchangeable probes for Total Chlorine\* (Code 1732) and ORP (Code 1734) measurement in water. Replacement pH Probe (Code 1733)
- Auto-off after 10 minutes
- Power: Four 3VCR-2032 batteries
- Requires 7044A-J Tablets (included)

# pH/TDS/SALT Tracer

#### Code 1766 · NH (1)

#### Features:

- Measures five parameters including Conductivity, TDS, Salinity, pH and Temperature using one electrode
- Units of measure: pH, µS, mS, ppm, ppt, mq/L, °C, °F
- Memory stores up to 25 labeled readings
- Adjustable Conductivity to TDS ratio
- Auto power off and low battery indicator

#### Options:

- Replacement Electrode for 1766 only, Code 1755
- Weighted Stand w/Sample Cups [5], Code 1746
- Sample Cups w/caps (24), Code 1745

	Range	Resolution	Accuracy
Conductivity	0 to 199.9 $\mu\text{S},$ 200 to 1999 $\mu\text{S},$ 2.00 to 19.99 mS	0.1 µS	±1%
TDS/Salinity	0 to 99.9 ppm (mg/L), 100 to 999 ppm (mg/L), 1.00 to 9.99 ppt	0.1 ppm (mg/L)	±2%
рН	0.00 to 14.00 pH	0.01 pH	±0.01 pH
Temperature	32° to 149°F (O to 65°C)	0.1°F/°C	±1.8°F/°C

Code 1766



ON €LaMott

Weighted Stand Code 1746

Sample Cup Code 1745

# pH Buffer Solutions

These Standardized pH Buffer Solutions are for use in calibration of pH meters. Available in 120 mL and 500 mL sizes.

pH Value*	Code
4.01	2866
7.00	2881
10.00	2896

Other pH values available.



# **Conductivity/TDS Solutions**

The following potassium chloride solutions can be used to standardize conductivity meters. TDS values are based on a 0.7 conversion from conductivity. Available in 30 mL and 500 mL sizes.

Code	Description
6312-L	84 µS/cm, 59 ppm
6354-L	1,413 µS/cm,989 ppm
6317-L	12,880 µS/cm, 9016 ppm



# METERS & ACCESSORIES

# **Dissolved Salts**

High levels of soluble salts in the soil can be caused by excessive fertilization, insufficient watering, poor drainage, or by some contributing salt water intrusion. High concentrations of soluble salts can inhibit plant growth and will reduce overall crop yields. Greenhouse plants and other sensitive crops may be damaged if soluble salts exceed 2000 ppm. Soluble Salts, or Total Dissolved Salts, are measured by means of a Conductivity Meter. A conductivity reading measures the capacity of a solution to conduct an electric current and is directly related to the total ionic concentration of dissolved substances in the solution. Thus, the conductivity reading of a soil extract can be converted into a reading of Total Dissolved Salts to indicate combined levels of sulfates, chlorides and other salts in the soil. Extract is prepared using deionized water, not included with meters.

# LaMotte TDS 6 Series Meter

TDS 6 (without carrying case) · Code 5-0036-02 · NH (3)

#### TDS 6 (with carrying case) includes two calibration standards · Code 5-0037-02 · NH (5)

Microprocessors have enabled meter manufacturers to combine many features into smaller designs with better accuracy. Meter includes electrode and temperature probe, and is available with or without a carrying case.

**€**LaMotte

#### Features:

- Push button operation
- Calibration 1 per range
- Range: 0.0-10.0, 100.0, 1,000 ppm, 1.0-10.00, 100.0, 200 ppt

Code 5-0037-02

- Power: Four AAA batteries included
- Temperature readout 0-100°C/0.1°C
- Automatic Temperature Compensation
- Auto-off after 17 minutes
- Hold function
- Adjustable conductivity to TDS factor
- Instructions included for measuring TDS in soil
- Meter has a two-year warranty

Code 5-0036-02



See back page for Shipping Codes & Weights chart.

# SAL/EC/TDS Tracer

#### Code 1749 · NH (1)

#### Features:

Easy to use

TRACER

PockeTester

MODE

CAL

ᅇᆣ

€LaMotte

- 2% accuracy for EC, TDS and Salt modules
- Automatic temperature compensation
- Self calibration
- Memory can store up to 15 readings
- Automatic shut-off and low battery indicator; uses four 3V CR-2032 button batteries
- Auto Off after 10 minutes

#### Options:

- EC/TDS/SAL Replacement Electrode · Code 1765
- Weighted Stand w/Sample Cups (5) · Code 1746
- Sample Cups w/caps (24) · Code 1745
- Conductivity Standard, 84 µS · Code 6312
- Conductivity Standard, 1413 µS · Code 6354
- Conductivity Standard, 12,880 μS · Code 6317





Sample Cup

Weighted Stand

	Range
Conductivity:	0 to 199.9 μS, 200 to 1999 μS, 2.00 to 19.99 mS
TDS:	0 to 99.9 ppm (mg/L), 100 to 999 ppm (mg/L), 1.00 to 9.99 ppt (g/L)
Salinity:	0 to 99.9 ppm, 100 to 999 ppm, 100 to 9,900 ppm
Accuracy:	EC, TDS, Salt: ± 2% FS; Temperature: ± 1°C (1.8°F)
Temperature	±1.8°F/°C



# Conductivity/TDS Solutions

The following potassium chloride solutions can be used to standardize conductivity meters. TDS values are based on a 0.7 conversion from conductivity. Available in 30 mL and 500 mL sizes.

Code	Description	Size
6312-L	84 μS/cm, 59 ppm	500 mL
6354-L	1,413 µS/cm,989 ppm	500 mL
6317-L	12,880 µS/cm, 9016 ppm	500 mL

# ELECTRONIC LABS

#### Model SCL-12 · Code 1985-05 · LQ (37) Reagent Refill · Code R-1985-04 · LQ

See back page for Shipping Codes & Weights chart.

#### Model SCL-15 w/out pH & Dissolved Salts Meters Code 1988-03 · LQ (33)

The LaMotte Model SCL-12 is designed to provide the landowner, consultant, or fertilizer specialist with a method for achieving immediate and economical soil analyses in the field without sacrificing accuracy. The Model SCL-12 is a self-contained, electronic soil analysis laboratory that provides accurate answers anywhere for 15 soil factors, including available forms of macronutrients and critical micronutrients. The SMART® 3 Colorimeter instantly analyzes color reactions developed in nutrient tests. Display readings are multiplied by a conversion factor specific to each test to provide a result in parts per million (ppm) or pounds per acre (lb/acre)—no further calculations are necessary. The simplified test

procedures provide at least 20 tests for each soil nutrient. Each accurately standardized system is furnished in an individual plastic module for quick distinction. All tests are performed in minutes on easy-to-prepare soil extracts, based on **Mehlich I extraction**. Critical soil pH measurements are performed quickly and reliably with a battery-powered pH 5 meter. The meter measures

> the pH of a one-to-one solution of soil and distilled water over the range of 0-14 pH units to a sensitivity of ±0.01 pH. Soluble Salt levels in soils and irrigation waters are monitored accurately with a TDS 6 meter, measuring Dissolved Salts from 0-999+ ppm.

Code 1985-05

All of the LaMotte soil test kits measure the portion of the soil nutrient that is available for the plant to use. Pounds per acre represent the number of pounds of soil in an acre to the plow depth of 6-7 inches, or 2,000,000 lbs.

EaMotte

SMART3

Colorimeter Tests	Method	Range*	# Tests
Nitrate Nitrogen*	Cadmium Reduction	0-300 lb/acre	20
Nitrite Nitrogen	Diazotization	0-40 lb/acre	20
Ammonia Nitrogen*	Nesslerization	0-200 lb/acre	50
Phosphorus*	Ascorbic Acid Reduction	0-99 lb/acre	50
Potassium*	Tetraphenylboron	0-500 lb/acre	100
Sulfur	Barium Chloride	3-94 ppm	50
Copper	Diethyldithiocarbamate	0-30 ppm	100
Iron	Bipyridyl	0-30 ppm	50
Manganese	Periodate	0-75 ppm	50
Zinc	Zincon	0-15 ppm	50
Direct Reading Titrator Tests: Range* # Tests			
Calcium			0
Magnesium	0-2400 lb/acre		
Chloride	0-1000 lb/acre	50	D
Battery-Powered Meters: Range*			
рН 5	pH 0-14		

рнэ	μH 0-14		
TDS 6	0-10.00, 100.0, 1,000 ppm; 1.00-10.00, 100, 200 ppt		
See table at right for unit	See table at right for unit conversion factors		

#### **Unit Conversion Factors:**

Results can be measured using a choice of units, explained here. Parts per million (ppm), pounds/acre and Kg/hectare units can be converted to each other using these values:

Area	Soil Depth	Soil Weight
1 acre	6-7 inches	2 million lb
1 hectare	15-18 cm	2.25 million Kg
ppm	lb/acre	Kg/hectare
ppm 0.5	lb/acre 1	Kg/hectare 1.12
		2.

A number of variables must be considered when interpreting soil test results in addition to the values obtained. These variables include the composition of the soil, drainage, climate, previous fertilizer programs and the type of plant to be grown. Samples must also be truly representative of the area being studied and must be carefully selected.

# AGRICULTURAL COMBINATION SOIL OUTFITS

Code 5010-01

See back page for Shipping Codes &

Weights chart.

## **Model STH Series**

#### Macronutrients & pH

Model STH-4 · Code 5029 · LQ (10) Reagent Refill · Code R-5029 · LQ (5)

#### Macronutrients, pH, Humus, Calcium, & Magnesium

Model STH-7 · Code 5061 · LQ (12) | Reagent Refill · Code R-5061 · LQ (6)

#### Macronutrients, pH, & Humus

Model STH-5 · Code 5007 · LQ (12) | Reagent Refill · Code R-5007 · LQ (6)

#### Macronutrients, Micronutrients, & pH

Model STH-14 · Code 5010-01 · LQ (20) | Reagent Refill · Code R-5010-01 · LQ (10)

The Model STH Combination Soil Outfits have offered simplified methods for determination of available nutrients found in agricultural soils for over 50 years. Since the original introduction, based on Morgan soil test methods, reagent systems have been updated with new advancements. A series of chemical tests use standardized reagents to produce color reactions measured against laminated color charts. All STH outfits come in lightweight carrying cases with components securely mounted in removable trays. This provides flexibility for the in-house specialist who also wants to make quick problem determinations in the field. Colorimetric test methods are used for most test factors. Tests for calcium, sulfate and chlorides are based on turbidity measurements. Potassium analysis also employs a turbidity measurement, using a unique reading device designed in LaMotte laboratories to read directly in pounds per acre. A single extraction procedure, using Morgan Universal Extraction Solution, provides the liquid soil extract for all the nutrient tests with the exception of chloride, which is extracted with demineralized water. The Humus Screening Test, performed on a soil sample-demineralized water suspension, employs five color standards for rapid measurement of humus content of the soil. Soil pH is determined colorimetrically, using pH indicators and color charts covering the range of pH 3.8 to 9.6. The STH outfits also include simplified procedures for screening nitrates, phosphorus and potassium in plant tissues. Complete reagent refill packages are available for each STH outfit. Kits includes instructions, a soil management handbook and a pad of soil analysis report forms. The LaMotte Soil Handbook contains general information on interpretation of test results for determination of lime and fertilizer requirements.

#### STH-4 · CODE 5029

Test Factor	Tests	Range*
рН	100	рН 3.8-9.6
Nitrate Nitrogen	50	10-150 lbs/acre
Phosphorus**	50	10-200 lbs/acre
Potassium	50	100-400 lbs/acre

#### STH-5 · CODE 5007

Test Factor	Tests	Range*
рН	100	рН 3.8-9.6
Nitrate Nitrogen	50	10-150 lbs/acre
Phosphorus**	50	10-200 lbs/acre
Potassium	50	100-400 lbs/acre
Humus (Organic Matter)	50	L-H 1½%-8%

#### STH-7 · CODE 5061

Test Factor	Tests	Range*
рН	100	рН 3.8-9.6
Nitrate Nitrogen	50	10-150 lbs/acre
Phosphorus**	50	10-200 lbs/acre
Potassium	50	100-400 lbs/acre
Humus (Organic Matter)	50	L-H 1½%-8%
Calcium	50	150-2800 ppm
Magnesium	50	L-H 5-150 ppm

#### STH-14 · CODE 5010-01

Test Factor	Tests	Range*
рН	100	рН 3.8-9.6
Nitrate Nitrogen	50	10-150 lbs/acre
Phosphorus**	50	10-200 lbs/acre
Potassium	50	100-400 lbs/acre
Humus (Organic Matter)	50	L-H 1½%-8%
Calcium	50	150-2800 ppm
Magnesium	50	L-H 5-150 ppm
Ammonia Nitrogen	50	L-H 5-150 ppm
Manganese	50	L-H 4-40 ppm
Aluminum	50	L-H 5-125 ppm
Nitrite Nitrogen	50	1-50 ppm
Sulfate	50	50-2000 ppm
Chloride	50	25-500 ppm
Ferric Iron	50	5-125 lbs/acre

See page 5 for unit conversion factors

+ For non-alkaline soils. Code 5090 Phosphorus Auxiliary package recommended for alkaline soils.

# **GARDEN & EDUCATION OUTFITS**



# Model EL Garden Kit

#### Model EL · Code 5679-01 · LQ (4) · Reagent Refill · Code R-5679 · R2 (3)

A simple test kit for soil science education or garden analysis. Rapid test procedures, diagramed instructions and laminated color charts are used to measure concentrations of nitrogen, phosphorus, potassium [15 tests each] and soil pH [30 tests]. The Study of Soil Science handbook, LaMotte Soil Handbook and Garden Guide Manual are included to interpret test results and give lime and fertilizer recommendations.

# Educational Test Kits

Kits are supplied with unit dose, non-hazardous TesTabs<sup>®</sup>. Sufficient tablets to run 50 repetitions of each test factor. Simple diagrammed instructions, hardware and laminated color chart included.

#### Soil NPK Kit · Code 3-5880 · NH (1)

#### Features:

- Tests for nitrogen, phosphorous and potassium
- Results reported as Low, Medium and High





See back page for Shipping Codes & Weights chart.

ELON



Soil pH Kit · Code 5912 · NH (1) Features:

• Tests for pH in the range of 4.0-11.0 in 1.0 pH units







# рН

Model ST-M · Code 5023-01 · R2 (3)

#### Model ST-T · Code 5024 · R1 (1)

The pH value affects all mineral elements and the biological processes made available to plants from the soil. Accurate pH testing is essential to determine lime requirements and to insure that a mineral-rich soil is also a fertile one.

Code/Model	Method	Range & Sensitivity	Reagent System	# of Tests
5023-01/ ST-M	5 Color Charts & Spot plate Morgan Method	pH 3.8-8.4 in 0.2 increments (not for heavy clays)	5 individual pH indicators	50
5024/ST-T	Color Chart & Spot Plate	pH 4.0, 5.0, 6.0, 7.0, 8.0	Duplex Indicator	100

## Texture

#### Code 1067 · NH (2)

The overall texture of a soil affects growth in the root zone, which determines the above-ground growth production, and is determined by the fractions of sand, silt and clay present.

Code	Method	Range & Sensitivity	Reagent System	# of Tests
1067	Settling	Determines sand, silt, & clay fraction, texture determined by chart	Dispersion, Flocculation	50

# **Plant Tissue Testing**

Plant tissue testing provides essential information concerning plant use of nutrients vital to their growth. These simplified field tests for green plant tissue indicate whether growing plants are receiving adequate amounts of available nutrients from the soil. All tests give qualitative results for the specific nutrients. By comparing test results from healthy and problem plants, it is possible to pinpoint deficiencies or excessive nutrient conditions.

# Macronutrient Plant Tissue Kit

#### Model PT-3R · Code 5026-01 · LQ (3) Reagent Refill · Code R-5026 · LQ (2)

A complete kit for determining nitrates, phosphorus and potassium in plant tissue. Diced green plant tissue is saturated in a Universal Extracting Solution to prepare a single liquid extract for use with all three tests. **Qualitative results given as abundant, adequate, deficient only.** Reagents for 50 tests per factor.

# **Micronutrient Plant Tissue Kit**

# Model PT-04 · Code 5261-01 · R1 (3)

#### Reagent Refill · Code R-5261 · R1 (2)

Includes tests for ferrous and ferric iron, zinc, copper, manganese and boron. Each test is made from the sap of plant tissues, which is extracted by squeezing the tissue with pliers. Comparative tests are made between a healthy plant and a similar one showing deficiency symptoms. **"Spot" tests indicate presence or absence only.** Reagents for 50 tests each factor.



# HYDROPONICS OUTFITS

See back page for Shipping Codes & Weights chart

Hydroponic culture is the growing of plants in a controlled environment with nutrient solutions, but without the use of soil as the supporting medium. Plant roots are fed directly, which is in contrast to conventional growing methods where plant food is applied to the soil and the roots extract the nutrients from the soil. Plants are either grown directly in nutrient solutions with only structural support or in beds through which nutrient solutions are periodically recirculated. Unlike field crops, hydroponically grown plants can be grown at great densities and with less concern about diseases initiated in soils or by insects and weeds. Hydroponics has played a significant role in modern plant nutrition research. Scientists are able to isolate the effects of essential minerals on various stages of plant growth and to study the effects of single element deficiencies under controlled conditions.

# Hydroponics 4-In-1 Test Kit

#### Model HP-1 · Code 3561-01 · LQ (7) · Reagent Refill · Code R-3561 · LQ (2)

An abbreviated version of our popular Model AM-41, the new Model HP-1 offers tests for pH and three key nutrient factors: nitrogen, phosphorus and potassium. It allows the hydroponic hobbyist to maintain proper nutrient balance and to achieve optimum growing conditions in soil-less cultures. Reagents sufficient for 50 tests per factor and complete labware are foam-mounted in a sturdy carrying case. Instructions and 75-page Hydroponics Handbook are supplied.

Octa-Slide 2 Comparator Tests pH pH 4.5-8.0		
hii a'?-o'o		
5-200 ppm*		
3-30 ppm		

Direct Reading	Turbidity Tube
Potassium	0-250 ppm



# pH Hydroponics Test Kit

Model HPH · Code 5074-01 · R1 (1) · Reagent Refill · Order 5132-G · R1 (1)



Simply add pH indicator reagent to the sample solution in a test tube for a color reaction. The resulting color is read in an Octa-Slide 2 Comparator with permanent color standards for pH values of 4.8, 5.2, 5.6, 6.0, 6.4, 6.8, 7.2 and 7.6. The kit has sufficient reagent for 50 tests and is packaged in a sturdy, hinged box.



Code 5074-01

# SAMPLING EQUIPMENT

# **Professional Soil Sampler**

#### Coring Tube, 3 ft (1 m) · Code 1016 · NH (6)

This chrome-plated steel sampler takes samples in all types of soils to a depth of 3 feet [1 m]. The 12 inch [30 cm] sampling tube has a durable cutting tip and a cutaway wall for inspection and easy removal of the soil core. Attach the tube directly to the 12 inch [30 cm] handle bar or interpose one or both 12 inch [30 cm] extension rods, depending on desired sampling depth. The extension rods are marked at 6 inch [15 cm] intervals for accurate measurement of sampling depth.

# **Basic Soil Sampler**

#### Model EP · Code 1055 · NH (2)

The galvanized steel sampler has a saw-toothed cutting edge tapered for easy core removal. The cutaway side of the tube permits inspection of soil core. The Model EP takes a one-inch core sample to a depth of 10 inches [25 cm] and is furnished with 20 LaMotte Soil Sampling Bags.



Code 1055

# **Spot Plate**

#### Plastic, Two-Well Code 0159 · NH (1)

White plastic. Two wells. 24mm x 8mm deep. Draining channels 8mm wide x 3mm deep run to smaller wells 10mm diameter x 4mm deep. Plate is 85mm x 75mm.






## Soil Sampling Bags

#### Package of 100 Code 0615-J · NH (2)

These 6 x 4 inch (15 x 10 cm) plastic zip-lock bags have instructions for collection and preparation of soil samples printed directly on each bag. By preventing contamination or accidental mixing of different samples, these convenient soil bags help insure accurate test results.

Code 1016


# HANDBOOKS & CATALOGS




## LaMotte Soil Handbook Order Code 1504

Staff, LaMotte Company

This 60-page "growers' manual" discusses major and minor nutrients, trace elements, soil pH, organic matter, soil texture, etc. Includes lime and fertilizer recommendations for a variety of crops and plants, and pH preferences for over 700 plants.





Dr. Robert Stegner

## Plant Nutrition Studies Order Code 1596

This 76-page manual covers the study and practice of hydroponics: plant culture in soil-less nutrient solutions. Includes a series of laboratory procedures and open-ended investigations.

# A Study Of Soil Science Order Code 1530

Dr. Henry D. Foth

This 44-page booklet provides an introduction to soil formation, soil pH, mineral elements, plant nutrition, the life cycle of growing plants and soil fertility management.



## Aquaculture Testing Products Order Code 1612 Test kits and instrumentation designed for the fish farm, hatch-

OTHER LAMOTTE CATALOGS

eries, and research institutions. Equipment designed for the fish farm, natcheries, and research institutions. Equipment designed for monitoring water quality conditions on-site and for benchtop locations. Test equipment also featured for the aquarium hobbyist, the retailer, and the ornamental culturist.

## Water Quality Testing Products Order Code 1653

A complete guide to instruments, apparatus, kits, and reagents. This catalog features the best available test equipment for testing a variety of waters. LaMotte individual and combination kits, and instrumentation are featured.

#### Environmental Science Products Order Code 1590

"Hands-on" test equipment for air, soil, and water chemistry students in elementary, secondary, vocational, outdoor, and college science programs.

# Food & Beverage Safety Products

# ELCMORE

#### Order Code 1658

Contains information on test strips, kits and instruments for the Food and Beverage Industry. Products focusing on safety and sanitation.

# Shipping Codes & Weights

The shipping code in the product description will refer to one of the following in this chart. Weight will be in pounds and enclosed in ( )

CODE	DESCRIPTION
NH	Non-Hazardous Material, No Fees
HF	Hazardous Material, Air & Ground Fees
R1	Small Qty. Hazardous Material, No Fees
R2, R3, LQ	Hazardous Material, Air Fees Only



LaMotte Company · PO Box 329 Chestertown · Maryland · 21620 · USA t: 800-344-3100 · 410-778-3100 f: 410-778-6394 · www.lamotte.com

#### WATER QUALITY Testing Product Corder A comp This car

